



Possible to record 10,000 data sets



Animal Body Temperature Logger



With endorectal probe for mice



With endorectal probe for rats



Cable length: approx. 1 m



High precision, platinum RTD^{*1} sensor (in an anti-corrosive SUS316 protective tube)

*1 Resistance Temperature Detector
Tolerance: $\pm(0.15 + 0.002 \times t)^\circ\text{C}$
t: Absolute value of the measured temperature



The round-shaped tips minimize stress and pain felt by animals!

Recording data




Simply press the START key to start recording measurements. The interval for data capture can be set between 1 second and 60 minutes.

On top of animal body temperature, four environmental data – temperature, humidity, barometric pressure and vibration – will also be recorded simultaneously (sensors for these measurements are built in the main unit).^{*2}

*2 The items to be shown on the display can be chosen.

Continued overleaf...

Sending the recorded data to a PC



Connect the main unit to a PC using the provided USB cable. The PC will recognize the device, and transfer of data (in CSV format) will become possible. The data file will look as shown on the left (containing columns for data no., date, time, temperature and others).

Specifications

	Resolution	Measurement range	Accuracy
Endorectal probe			
Temperature	0.1 °C 0.1 °F	0 to 80 °C 32 to 176 °F	±0.4 °C (0 to 80 °C) ±0.7 °F (32 to 176 °F)
Environment sensors			
Temperature	0.1 °C 0.1 °F	0 to 60 °C 32 to 140 °F	±0.5 °C (20 to 30 °C) ±0.9 °F (68 to 86 °F)
Relative humidity	0.1% RH	0 to 100%	±3% (20 to 80%)
Barometric pressure	0.1 hPa	500 to 1100 hPa	±3 hPa (0 to 60 °C)
Vibration	1 mG	0 to 2000 mG	±20%, static acceleration
Data capacity	Maximum 10,000 sets (including date and time)		
Power supply	Two LR6 (AA) batteries, RS-232C, or USB		
Battery life	Approx. 6 months (with measurement interval at 1 minute, alkaline batteries)		
Clock accuracy	Maximum ±1 minute/month		
Operating environment	0 to 60 °C/32 to 140 °F, 85% RH or less (no condensation)		
Dimensions (main unit)	127 (W) × 90 (H) × 36 (D) mm (including the protector)		
Weight (main unit)	Approx. 255 g (including batteries and the protector)		

Dedicated stand
(sold separately)



A&D Company, Limited

3-23-14 Higashi-Ikebukuro, Toshima-ku, Tokyo 170-0013 JAPAN
Telephone:[81](3) 5391-6132 Fax:[81](3) 5391-6148
http://www.aandd.jp

A&D ENGINEERING, INC.

1756 Automation Parkway, San Jose, CA 95131 U.S.A.
Telephone:[1](408) 263-5333 Fax:[1](408) 263-0119

A&D Australasia Pty Ltd.

32 Dew Street, Thebarton, South Australia 5031 AUSTRALIA
Telephone:[61](8) 8301-8100 Fax:[61](8) 8352-7409

A&D INSTRUMENTS LTD.

Unit 24/26 Blacklands Way Abingdon Business Park,
Abingdon, Oxon OX14 1DY UNITED KINGDOM
Telephone:[44](1235) 550420 Fax:[44](1235) 550485

<German Sales Office>

Hamburger Straße 30 D-22926 Ahrensburg GERMANY
Telephone:[49](0) 4102 459230 Fax:[49](0) 4102 459231

A&D KOREA Limited

817, Manhattan Bldg., 33, Gukjegeumyung-ro 6-gil,
Yeongdeungpo-gu, Seoul, 150-749, KOREA
Telephone:[82](2) 780-4101 Fax:[82](2) 782-4280

A&D RUS CO., LTD.

Vereyskaya str.17, Moscow, 121357 RUSSIA
Telephone: [7] (495) 937-33-44 Fax: [7] (495) 937-55-66

A&D Instruments India Private Limited

509 Udyog Vihar Phase V
Gurgaon-122 016, Haryana, INDIA
Telephone: [91](124) 471-5555 Fax: [91](124) 471-5599