

3590EXT3GD

3590E "ENTERPRISE" 3GD series: WEIGHT INDICATOR FOR ADVANCED APPLICATIONS IN ATEX 2 & 22 ZONES



Weight indicator for ATEX areas classified at risk of explosion with protection methods according to

ATEX II 3G Ex nR IIC T6 Gc X for gases

ATEX II 3D Ex tc IIIC T85°C Dc IP68 X for dust.

The wide range of available software program guarantees the maximum versatility. Completely programmable printouts and fitted with alibi memory. CE-M approvable (OIML R-76 / EN 45501).



The best solution  
for advanced industrial  
applications

## MAIN FEATURES

- 25-key alphanumeric waterproof keyboard.
- Highly efficient red LED display with 6 digits 15mm high.
- Backlit LCD graphic 25x100mm display.
- Synoptic bar graph with 16 bright LEDs showing the active functions.
- Easy to clean STAINLESS STEEL waterproof IP68 enclosure; resistant to harsh and corrosive environments.
- Dimensions: 264x115x174 mm.
- Suitable for use on the table, column, or wall.
- Real time clock and permanent data storage.
- Fitted with alibi memory, integrated on the motherboard.
- Functions available with DINI TOOLS utility
  - Configuration, calibration, data entry and print formatting.
  - Recording and filing of all the information on PC.
  - Complete retrieval of the saved data for quick replacement.
  - Instrument calibration with numeric values.
- Selection of the programme language directly in the set-up.
- 24-bit A/D converter, 4 channels, up to 3200 conv./sec. and up to 8 signal linearisation points.
- Up to 10.000e OIML or 3 x 3000e @ 0,3  $\mu\text{V/e}$  CE-M legal for trade.
- Up to 1.000.000 displayable divisions for internal factory use, with internal resolution up to 3.000.000 points.
- 110-240 Vac power supply.
- Management of up to 4 independent scales (up to 2 for the AF03 version).
- Connectable with up to 16 analogue 350-Ohm (or 45 1000-Ohm) load cells.
- Connectable to printers and labellers with the command drivers.

## MAIN CERTIFICATIONS

- EU Type Examination Certificate (45501:2015)
- OIML R76
- OIML R51 - MID
- OIML R134 (AF09)
- Australian legal for trade certificate of approval (NMI S788)

## I/O SECTION

- Two RS232 serial ports, for connection to printer (in safety zone), PC or PLC.
- One RS232/RS485 serial port, for connection to printer (in safety zone), PC or PLC.
- 4 optoisolated outputs (16 in the IO versions).
- 2 optoisolated inputs (8 in the IO versions).
- Profibus interface to install in safety zone (available upon request for E-AF01 and E-BATCH1 versions).
- Analogue output with D/A converter at 16 bit, 0-10Vdc, 0-20mA, 4-20mA (available upon request for the IO versions).



“YOUR WORLDWIDE PARTNER FOR WEIGHING,”

DINI ARGEO  
FRANCE sarl  
France

DINI ARGEO  
GMBH  
Germany

DINI ARGEO  
UK Ltd  
United Kingdom

DINI ARGEO WEIGHING  
INSTRUMENTS Ltd  
China

DINI ARGEO  
OCEANIA  
Australia



**COMPANY HEADQUARTERS**

Via Della Fisica, 20  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 843418

**SERVICE ASSISTANCE**

Via Dell'Elettronica, 15  
41042 Spezzano di Fiorano Modena • Italy  
Tel. +39.0536 921784



SALES AND TECHNICAL ASSISTANCE SERVICE