

## GX-K / GF-K Features & Benefits

Features	Benefits
SHS sensor	1.5 second ultra fast response speed and minimal maintenance costs
VFD display	Display easy to read in any place
IP65	Washable waterproof and dust proof, it can be used in adverse environments
Automatic calibration (GX-K) with built in weight	According to temperature change, it automatically calibrates by means of the internal mass weight, so the weighing measurement is always accurate
Standard RS232C interface	Easy to communicate with PC, Printer
Standard WinCT software	Easy to collect data from the balance to a PC
ID Number	Used to identify the balance when GLP is used
Auto power on function	Plug it in and it turns itself on automatically without need to press ON/OFF key
Display auto power off function	Display turns off after 10 minutes of inactivity, saving energy
Data memory function	Weight data can be memorized, and the balance can print these via a printer, or can transmit data to a computer in a different location
Smart range function (GX/GF-8K2/32K only)	Fine weighing is possible even with a heavy container for greater accuracy
Time & Date (GX only)	Standard Time & Date function complies with GLP and interval weighing in data memory function or in print out.
Automatic adjustable environment setting (GX-K only)	Adapts to the most suitable environment response setting automatically with one-touch key operation
Interval time setting	Weight data can be memorized, and printed out for every interval setting time
Auto re-zero function	Re-zeros automatically after data output; weights can be added continuously until the balance reaches its full scale (100%)
Multiple weighing units and programmable unit	Uses programmable or standard units of measurement
Animal Weighing mode	Allows quick and accurate determination of the weight of any live or unstable subject
Counting mode	Allows counting and inventory management by the balance
ACAI function	Improved counting accuracy
Comparator function	Hi, OK, or LO is indicated on the display as the comparison result
Overall capacity indication	Risk of overloading the balance is minimized
Waterproof RS232C cable 25pin-9pin 5m(option)	Enables communication with PC in an environment where waterproofing is needed